

Technical Data Sheet of Chloroprene Latex CRL-50LK

Chemical Name: Cationic Chloroprene Latex

CAS NO.: 9010-98-4

Technical Data of Chloroprene Latex CRL-50LK:

Items	Index
Appearance	White or white milk emulsion
Solid Content% Min	50
Viscosity (mPa.s)	10-35
Surface Tension (N/m*10 ⁻³)	20-40
Density(g/cm ³)	1.100

Application:

1. This product possesses characteristics similar to chloroprene rubber and exhibits diverse applications including: the modification of cement to produce elastic cement, the dressing of ship decks, and the creation of rigid waterproof layers.
2. It can be used to modify asphalt for the formulation of chloroprene latex asphalt waterproof coatings.
3. It is applicable in the processing of paper, fiber impregnation, and the preparation of adhesives, facilitating the bonding of materials such as cement, wood, and fiberglass.
4. It can serve in the development of fireproof materials.

Package:

Packed in plastic drum, net weight 1100kg±2kg

Storage:

The product must be stored and transported in a manner that ensures it remains well-ventilated and dry. Its packaging should keep away from light and sunlight.

The recommended storage temperature ranges from 5°C to 30°C.

The product has a shelf life of six months if maintained at temperatures below 23°C, starting from the date of production.