江苏象化科技有限公司
JIANGSU ELEPHCHEM HOLDING LIMITED

Technical Date Sheet of VAE Emulsion CW 40-707A

Product name: Vinyl Acetate-Ethylene Copolymer Emulsion CW 40-707A
CAS NO.: 24937-78-8

Technical Data of VAE Emulsion CW 40-707A:

Items	Specifications
Appearance	White emulsion or light yellow and free of suspended matter
Solid content (%)	≥54.5
Viscosity (mpa.s, 25℃)	500～1000
pH	4.0~5.5
VAC (%)	≤0.3
Ethylene(%)	14.0-18.0
Particle size (μm)	0.2~2.0
Dilution stability (%)	≤3.5
Free Formaldehyde (g/kg)	≤100
Minimum film formation temperature(℃)	≤1

Application:

1. Versatility: VAE Emulsions Are Highly Versatile And Can Be Tailored To Meet Specific Requirements In Different Industries.

2. Adhesives: VAE Emulsions Are Frequently Used In The Production Of Adhesives And Sealants. They Provide Excellent Adhesion To a Wide Range Of Substrates, Making Them Suitable For Applications Such As Woodworking, Paper Bonding, And Construction Adhesives.

JiangSu ElephChem Holding Limited

3. Paints And Coatings: VAE Emulsions Are Employed As Binders In Water-Based Paints And Coatings. They Contribute To The Film-Forming Properties Of These Products, Enhancing Their Durability, Adhesion, And Flexibility. They Are Also Known For Their Low Voc (Volatile Organic Compound) Content, Making Them Environmentally Friendly.
4. Textile Industry: In The Textile Industry, VAE Emulsions Are Utilized For Textile Coatings To Improve The Fabric's Water And Stain Resistance. They Also Enhance The Durability Of Printed Patterns.
5. Paper Industry: VAE Emulsions Are Used In Paper Coatings To Improve The Printability, Surface Finish, And Ink Holdout Properties Of Paper Products.
6. Construction: VAE Emulsions Find Applications In Construction Materials, Including Cement And Mortar Modifiers, Where They Improve Workability, Adhesion, And Durability.
7. Non-Woven Fabrics: VAE Emulsions Are Used In The Production Of Non-Woven Fabrics, Providing Strength And Flexibility To The Materials.
8. Emulsion Polymerization: They Serve As a Key Component In The Emulsion Polymerization Process To Produce Other Types Of Polymers And Latex Products.

Package:

Packages：In 25KG/50KG/220KG drum or 1000KG IBC drum.

Storage:

Store in accordance with local regulations on safe storage of chemical products.
Store in a dry, well-ventilated place. Stay away from hot objects, sparks, and other sources of ignition.
Incompatible with strong oxidants.

JiangSu ElephChem Holding Limited